

# TOLEDO

## FURNITURE

### Product Specification

**Brand:** Toledo Furniture  
**Product Series:** GIN Configured Furniture

#### Table Assembly

- Uses only UL listed electrical, data and communications components.
- Assembled using threaded mechanical fasteners through the leg frame assembly into the work surface to a torque of 6-10 ft. lbs.
- Suitable for use in a variety of connection and configuration methods including fixed or mobile, freestanding or modular group of tables.
- Reconfigurable to support a multitude of room arrangements and applications.
- Uses a fully welded 16 gauge tubular steel frame to support and stabilize the work surface to within 1/8".
- Includes a Lifetime warranty on all table frames, legs, raceways, and fabricated metal components and a 2-year warranty on work surface tops and laminates.
- Available 17 standard colors with customer custom color selection available.
- Custom configurable to enable the customer to design, configure and obtain a product exclusive to the customer's requirements, needs, desires, budget and application.
- Designed for frequent rearrangement, movement, rolling and lifting.

#### Work Surface

- Standard: 1-1/8" thick industrial grade 45 lb thermofused board.
- Alternate: .75" thick industrial grade 45 lb thermofused board.  
1-1/4" thick Solid Maple Block.  
1" thick Phenolic Resin.
- All laminate work surfaces have a phenolic backer sheet to balance the work surface.
- CNC routed for precision placement (within 1/32") of electrical, data and mounting devices.
- Configurable with the following materials and edges:
  - Post formed high-pressure laminate (HPL) on Top, Front, Sides and/or Back edges.
  - Color coordinating PVC edge banding in .020" or 3 mm thick as specified by the customer.
  - Work surface shall be configurable flush with or overhang the leg assembly up to 3" maximum on all sides as specified.
  - Available with any standard grade HPL high-pressure laminate from WilsonArt®, Formica®, Pionite® or Nevamar®.
  - Available in Chemical resistant Epoxy or Phenolic Resin, ESD (Electro Static Dissipative), Rubberized, or Solid Wood.
- Available in Round, Oval, Elliptical, Racetrack, Boat, Square, Rectangular, Hexagonal, Trapezoidal, Kidney, Flower, "C", Clover, Peninsula, Tombstone, Semicircle and custom shapes.

#### Leg and Frame Assembly

- GIN Frames are, "I" frame design with stabilizing gussets.
- Legs are constructed using 16 ga. steel tubing 2" dia. 16 ga. steel gussets and a fabricated 11 ga. foot assembly with 1.25" nylon non-staining leg levelers with heavy duty 5/16-18 screw-in stems
- All frames shall be constructed with full fillet electric arc welds to create a unitized frame assembly which is powder painted in a color as specified by the customer.

# TOLEDO

## FURNITURE

- Designed and available in size increments of ½” in depth, length and height.
- Shall use leveling glides or casters as specified.
- Height Adjustable tables are available 22”, 24”, 26-1/2”, 29”, and 32” with leveling glides or casters.
- All joints shall be square cut, butt-jointed and electric arc welded.
- Leg openings shall be fitted with polymer end caps.
- Legs at table ends shall have no cutouts or holes to provide a smooth clean finished appearance.

### **Troughs and Channels**

- Shall be full table length and have interior dimensions of 3”H x 20” x Table Length.
- Shall be capable of routing all electrical, data and communications lines in an enclosed assembly.

### **Optional: Modesty Panel**

- Modesty Panels are available in the following materials: HPL panels to match the work surface, or 18 ga. steel x 12”H x table length and assemble to the underside of the work surface with ¼” hardware.
- Available as a solid or perforated metal panel.

### **Optional: Casters**

- 3” or 4” diameter and rated to 100 lbs. each caster
- Supplied in pairs, 2 swivel and 2 swivel with brake.

### **Optional: Adjustable CPU Holder and CPU Rack**

- Adjustable CPU holder mounts underneath the work surface.
- Constructed of steel with adjustable width (5”-9½”) and height (15”-21”).
- Finish is smooth black powder coat.
- Verify leg & knee space before ordering. Unit includes mounting hardware and foam pads.
- The rack CPU holder mounts underneath the work surface at either a right or left side position.
- Expandable 6½” to 10” wide X 18” X 21”.
- Shall be slotted on both sides for air ventilation.